



- ① PATTERNED CONCRETE SHALL BE SMALL CANYON STONE TEXTURED PATTERN WITH A SECOND HIGHLIGHTING COLOR COMPLEMENTING FEDERAL COLOR 33105. ALL HIGHLIGHTING COLORS SHALL BE APPROVED BY THE TOWN.
- ② CONCRETE SHALL BE COLORED COMPLIMENTING FEDERAL COLOR 32516 AND BE UNIFORMLY DISTRIBUTED THROUGH THE CONCRETE. THREE SAMPLE COLOR PANELS SHALL BE PROVIDED TO THE TOWN FOR APPROVAL.

NOTES:

- 1. CONTRACTOR SHALL COORDINATE THE LOCATIONS OF ALL SIGN POSTS. CORING INTO CONCRETE IS NOT PERMITTED.
- 2. ANY MEDIAN TREES SHALL BE TRIMMED SO THE MINIMUM BRANCH HEIGHT IS 8' ABOVE THE GUTTER.
- 3. THE TOWN ENGINEER MAY REQUIRE A DRAINAGE SYSTEM IF AN IRRIGATION SYSTEM IS PROPOSED WITHIN THE MEDIAN.

**STANDARD DETAIL FOR RAISED MEDIAN
SPILL OR CATCH CURB**

NTS

