



DO NOT CUT OR DAMAGE LEADER, PRUNE DAMAGED OR DEAD BRANCHES AFTER PLANTING AND STAKING. PRUNE TO TYPICAL FORM OF SPECIES. DO NOT PRUNE UP LOWER BRANCHES.

SPECIFIED HEAVY DUTY TRUNK COLLAR ATTACHMENT. DO NOT TWIST.

14 GAUGE GALV. WIRE WITH 1/2" DIA. X 36" WHITE PVC PIPE ON ALL GUY WIRES. KEEP GUY WIRES CLEAR OF BRANCHES TO PREVENT RUB DAMAGE.

(3) SPECIFIED POSTS, 2" DIA., 6'-8' HIGH, ALIGN EQUIDISTANT AROUND TREE. KEEP PLUMB WITH TOPS EVEN. DRIVE 12" INTO UNDISTURBED SUBGRADE OUTSIDE PLANTING PIT. TREE STAKES LOCATED INSIDE WATERING SAUCER ON TREES GREATER THAN 3" CALIPER.

ROOT FLARE TO BE AT OR SLIGHTLY ABOVE THE FINISHED GRADE. SET TRUNK PLUMB. SEE NOTES AND SPECIFICATIONS IN SECTION 1500.

APPLY SPECIFIED MULCH AT 0" DEPTH AT TRUNK AND 4" DEPTH AT EDGE OF RING, INSIDE 4" WATERING SAUCER. REMOVE SAUCER UPON SODDING/ SEEDING IN IRRIGATED AREAS.

4" HIGH WATER SAUCER TO BE OUTSIDE DRIP LINE OF EVERGREEN TREES.

SPECIFIED BACKFILL MIXTURE. AMENDMENTS AS SPECIFIED IN TOP 12"

REMOVE ALL TWINE AND BURLAP FROM TOP 1/3 OF ROOTBALL. COMPLETELY REMOVE WIRE BASKET.

INITIAL STABILIZING BACKFILL 1/3 DEPTH, COMPACTED. SEE NOTES SPECIFICATIONS IN SECTION 1500.

UNDISTURBED PIT BOTTOM FOR ROOTBALL BASE.

- NOTES
1. GUYING AND STAKING TO BE REMOVED AFTER ONE GROWING SEASON.
 2. DO NOT PLANT ANY PLANT WITH A ROOTBALL THAT IS NOT IN COMPLIANCE WITH THE COLORADO NURSERY ACT REQUIREMENTS.

EVERGREEN TREE PLANTING

NTS



TOWN OF FREDERICK
STANDARDS & SPECIFICATIONS

1500-04